

Световые завесы и решётки, типа LCA 4

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: eai@nt-rt.ru || сайт: <https://euchner.nt-rt.ru/>

LIGHT GRIDS AND LIGHT CURTAINS

LCA 4



Benefits for you

- Safe monitoring options for any application
- Simple connection with M12 plug connector
- Safety category 4 and PL e according to EN ISO 13849-1
- ESPE type 4 according to DIN EN 61496-1
- Integrated evaluation
- Feedback loop connection



156506

LCA-4TR-14-1060-AP-156506

Light curtain LCA-4TR-14-1060

- Resolution 14 mm
- Protective field height 1060 mm
- Range 6 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product

**156507**

LCA-4TR-14-1210-AP-156507

Light curtain LCA-4TR-14-1210

- Resolution 14 mm
- Protective field height 1210 mm
- Range 6 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product

**156508**

LCA-4TR-14-1360-AP-156508

Light curtain LCA-4TR-14-1360

- Resolution 14 mm
- Protective field height 1,360 mm
- Range 6 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product

**156509**

LCA-4TR-14-1510-AP-156509

Light curtain LCA-4TR-14-1510

- Resolution 14 mm
- Protective field height 1510 mm
- Range 6 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)

- Installation material is included with the product



156500

LCA-4TR-14-160-AP-156500

Light curtain LCA-4TR-14-160

- Resolution 14 mm
- Protective field height 160 mm
- Range 6 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156510

LCA-4TR-14-1660-AP-156510

Light curtain LCA-4TR-14-1660

- Resolution 14 mm
- Protective field height 1660 mm
- Range 6 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156511

LCA-4TR-14-1810-AP-156511

Light curtain LCA-4TR-14-1810

- Resolution 14 mm
- Protective field height 1810 mm
- Range 6 m
- LED indicator for weak signal

- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156501

LCA-4TR-14-310-AP-156501

Light curtain LCA-4TR-14-310

- Resolution 14 mm
- Protective field height 310 mm
- Range 6 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156502

LCA-4TR-14-460-AP-156502

Light curtain LCA-4TR-14-460

- Resolution 14 mm
- Protective field height 460 mm
- Range 6 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156503

LCA-4TR-14-610-AP-156503

Light curtain LCA-4TR-14-610

- Resolution 14 mm
- Protective field height 610 mm

- Range 6 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156504

LCA-4TR-14-760-AP-156504

Light curtain LCA-4TR-14-760

- Resolution 14 mm
- Protective field height 760 mm
- Range 6 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156505

LCA-4TR-14-910-AP-156505

Light curtain LCA-4TR-14-910

- Resolution 14 mm
- Protective field height 910 mm
- Range 6 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156584

LCA-4TR-2B-510-AP-156584

Light grid LCA-4TR-2B-510

- 2 beams
- Protective field height 510 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156587

LCA-4TR-2B-510-AP-156587

Light grid LCA-4TR-2B-510

- 2 beams
- Protective field height 510 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156518

LCA-4TR-30-1060-AP-156518

Light curtain LCA-4TR-30-1060

- Resolution 30 mm
- Protective field height 1060 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156530

LCA-4TR-30-1060-AP-156530

Light curtain LCA-4TR-30-1060

- Resolution 30 mm
- Protective field height 1060 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156519

LCA-4TR-30-1210-AP-156519

Light curtain LCA-4TR-30-1210

- Resolution 30 mm
- Protective field height 1210 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156531

LCA-4TR-30-1210-AP-156531

Light curtain LCA-4TR-30-1210

- Resolution 30 mm
- Protective field height 1210 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156520

LCA-4TR-30-1360-AP-156520

Light curtain LCA-4TR-30-1360

- Resolution 30 mm
- Protective field height 1,360 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156532

LCA-4TR-30-1360-AP-156532

Light curtain LCA-4TR-30-1360

- Resolution 30 mm
- Protective field height 1,360 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156521

LCA-4TR-30-1510-AP-156521

Light curtain LCA-4TR-30-1510

- Resolution 30 mm
- Protective field height 1510 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156533

LCA-4TR-30-1510-AP-156533

Light curtain LCA-4TR-30-1510

- Resolution 30 mm
- Protective field height 1510 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156512

LCA-4TR-30-160-AP-156512

Light curtain LCA-4TR-30-160

- Resolution 30 mm
- Protective field height 160 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156524

LCA-4TR-30-160-AP-156524

Light curtain LCA-4TR-30-160

- Resolution 30 mm
- Protective field height 160 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156522

LCA-4TR-30-1660-AP-156522

Light curtain LCA-4TR-30-1660

- Resolution 30 mm
- Protective field height 1660 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156534

LCA-4TR-30-1660-AP-156534

Light curtain LCA-4TR-30-1660

- Resolution 30 mm
- Protective field height 1660 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156523

LCA-4TR-30-1810-AP-156523

Light curtain LCA-4TR-30-1810

- Resolution 30 mm
- Protective field height 1810 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156535

LCA-4TR-30-1810-AP-156535

Light curtain LCA-4TR-30-1810

- Resolution 30 mm
- Protective field height 1810 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156513

LCA-4TR-30-310-AP-156513

Light curtain LCA-4TR-30-310

- Resolution 30 mm
- Protective field height 310 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156525

LCA-4TR-30-310-AP-156525

Light curtain LCA-4TR-30-310

- Resolution 30 mm
- Protective field height 310 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156514

LCA-4TR-30-460-AP-156514

Light curtain LCA-4TR-30-460

- Resolution 30 mm
- Protective field height 460 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156526

LCA-4TR-30-460-AP-156526

Light curtain LCA-4TR-30-460

- Resolution 30 mm
- Protective field height 460 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156515

LCA-4TR-30-610-AP-156515

Light curtain LCA-4TR-30-610

- Resolution 30 mm
- Protective field height 610 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156527

LCA-4TR-30-610-AP-156527

Light curtain LCA-4TR-30-610

- Resolution 30 mm
- Protective field height 610 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156516

LCA-4TR-30-760-AP-156516

Light curtain LCA-4TR-30-760

- Resolution 30 mm
- Protective field height 760 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156528

LCA-4TR-30-760-AP-156528

Light curtain LCA-4TR-30-760

- Resolution 30 mm
- Protective field height 760 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156517

LCA-4TR-30-910-AP-156517

Light curtain LCA-4TR-30-910

- Resolution 30 mm
- Protective field height 910 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156529

LCA-4TR-30-910-AP-156529

Light curtain LCA-4TR-30-910

- Resolution 30 mm
- Protective field height 910 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156585

LCA-4TR-3B-810-AP-156585

Light grid LCA-4TR-3B-810

- 3 beams
- Protective field height 810 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156588

LCA-4TR-3B-810-AP-156588

Light grid LCA-4TR-3B-810

- 3 beams
- Protective field height 810 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156542

LCA-4TR-40-1060-AP-156542

Light curtain LCA-4TR-40-1060

- Resolution 40 mm
- Protective field height 1060 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156554

LCA-4TR-40-1060-AP-156554

Light curtain LCA-4TR-40-1060

- Resolution 40 mm
- Protective field height 1060 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156543

LCA-4TR-40-1210-AP-156543

Light curtain LCA-4TR-40-1210

- Resolution 40 mm
- Protective field height 1210 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156555

LCA-4TR-40-1210-AP-156555

Light curtain LCA-4TR-40-1210

- Resolution 40 mm
- Protective field height 1210 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156544

LCA-4TR-40-1360-AP-156544

Light curtain LCA-4TR-40-1360

- Resolution 40 mm
- Protective field height 1,360 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156556

LCA-4TR-40-1360-AP-156556

Light curtain LCA-4TR-40-1360

- Resolution 40 mm
- Protective field height 1,360 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156545

LCA-4TR-40-1510-AP-156545

Light curtain LCA-4TR-40-1510

- Resolution 40 mm
- Protective field height 1510 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156557

LCA-4TR-40-1510-AP-156557

Light curtain LCA-4TR-40-1510

- Resolution 40 mm
- Protective field height 1510 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156536

LCA-4TR-40-160-AP-156536

Light curtain LCA-4TR-40-160

- Resolution 40 mm
- Protective field height 160 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156548

LCA-4TR-40-160-AP-156548

Light curtain LCA-4TR-40-160

- Resolution 40 mm
- Protective field height 160 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156546

LCA-4TR-40-1660-AP-156546

Light curtain LCA-4TR-40-1660

- Resolution 40 mm
- Protective field height 1660 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156558

LCA-4TR-40-1660-AP-156558

Light curtain LCA-4TR-40-1660

- Resolution 40 mm
- Protective field height 1660 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156547

LCA-4TR-40-1810-AP-156547

Light curtain LCA-4TR-40-1810

- Resolution 40 mm
- Protective field height 1810 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156559

LCA-4TR-40-1810-AP-156559

Light curtain LCA-4TR-40-1810

- Resolution 40 mm
- Protective field height 1810 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156537

LCA-4TR-40-310-AP-156537

Light curtain LCA-4TR-40-310

- Resolution 40 mm
- Protective field height 310 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156549

LCA-4TR-40-310-AP-156549

Light curtain LCA-4TR-40-310

- Resolution 40 mm
- Protective field height 310 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156538

LCA-4TR-40-460-AP-156538

Light curtain LCA-4TR-40-460

- Resolution 40 mm
- Protective field height 460 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156550

LCA-4TR-40-460-AP-156550

Light curtain LCA-4TR-40-460

- Resolution 40 mm
- Protective field height 460 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156539

LCA-4TR-40-610-AP-156539

Light curtain LCA-4TR-40-610

- Resolution 40 mm
- Protective field height 610 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156551

LCA-4TR-40-610-AP-156551

Light curtain LCA-4TR-40-610

- Resolution 40 mm
- Protective field height 610 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156540

LCA-4TR-40-760-AP-156540

Light curtain LCA-4TR-40-760

- Resolution 40 mm
- Protective field height 760 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156552

LCA-4TR-40-760-AP-156552

Light curtain LCA-4TR-40-760

- Resolution 40 mm
- Protective field height 760 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156541

LCA-4TR-40-910-AP-156541

Light curtain LCA-4TR-40-910

- Resolution 40 mm
- Protective field height 910 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156553

LCA-4TR-40-910-AP-156553

Light curtain LCA-4TR-40-910

- Resolution 40 mm
- Protective field height 910 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156586

LCA-4TR-4B-910-AP-156586

Light grid LCA-4TR-4B-910

- 4 beams
- Protective field height 910 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156589

LCA-4TR-4B-910-AP-156589

Light grid LCA-4TR-4B-910

- 4 beams
- Protective field height 910 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156566

LCA-4TR-50-1060-AP-156566

Light curtain LCA-4TR-50-1060

- Resolution 50 mm
- Protective field height 1060 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156578

LCA-4TR-50-1060-AP-156578

Light curtain LCA-4TR-50-1060

- Resolution 50 mm
- Protective field height 1060 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156567

LCA-4TR-50-1210-AP-156567

Light curtain LCA-4TR-50-1210

- Resolution 50 mm
- Protective field height 1210 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156579

LCA-4TR-50-1210-AP-156579

Light curtain LCA-4TR-50-1210

- Resolution 50 mm
- Protective field height 1210 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156568

LCA-4TR-50-1360-AP-156568

Light curtain LCA-4TR-50-1360

- Resolution 50 mm
- Protective field height 1,360 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156580

LCA-4TR-50-1360-AP-156580

Light curtain LCA-4TR-50-1360

- Resolution 50 mm
- Protective field height 1,360 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156569

LCA-4TR-50-1510-AP-156569

Light curtain LCA-4TR-50-1510

- Resolution 50 mm
- Protective field height 1510 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156581

LCA-4TR-50-1510-AP-156581

Light curtain LCA-4TR-50-1510

- Resolution 50 mm
- Protective field height 1510 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156560

LCA-4TR-50-160-AP-156560

Light curtain LCA-4TR-50-160

- Resolution 50 mm
- Protective field height 160 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156572

LCA-4TR-50-160-AP-156572

Light curtain LCA-4TR-50-160

- Resolution 50 mm
- Protective field height 160 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156570

LCA-4TR-50-1660-AP-156570

Light curtain LCA-4TR-50-1660

- Resolution 50 mm
- Protective field height 1660 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156582

LCA-4TR-50-1660-AP-156582

Light curtain LCA-4TR-50-1660

- Resolution 50 mm
- Protective field height 1660 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156571

LCA-4TR-50-1810-AP-156571

Light curtain LCA-4TR-50-1810

- Resolution 50 mm
- Protective field height 1810 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156583

LCA-4TR-50-1810-AP-156583

Light curtain LCA-4TR-50-1810

- Resolution 50 mm
- Protective field height 1810 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156561

LCA-4TR-50-310-AP-156561

Light curtain LCA-4TR-50-310

- Resolution 50 mm
- Protective field height 310 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156573

LCA-4TR-50-310-AP-156573

Light curtain LCA-4TR-50-310

- Resolution 50 mm
- Protective field height 310 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156562

LCA-4TR-50-460-AP-156562

Light curtain LCA-4TR-50-460

- Resolution 50 mm
- Protective field height 460 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156574

LCA-4TR-50-460-AP-156574

Light curtain LCA-4TR-50-460

- Resolution 50 mm
- Protective field height 460 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156563

LCA-4TR-50-610-AP-156563

Light curtain LCA-4TR-50-610

- Resolution 50 mm
- Protective field height 610 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156575

LCA-4TR-50-610-AP-156575

Light curtain LCA-4TR-50-610

- Resolution 50 mm
- Protective field height 610 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156564

LCA-4TR-50-760-AP-156564

Light curtain LCA-4TR-50-760

- Resolution 50 mm
- Protective field height 760 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156576

LCA-4TR-50-760-AP-156576

Light curtain LCA-4TR-50-760

- Resolution 50 mm
- Protective field height 760 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156565

LCA-4TR-50-910-AP-156565

Light curtain LCA-4TR-50-910

- Resolution 50 mm
- Protective field height 910 mm
- Range 12 m
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product



156577

LCA-4TR-50-910-AP-156577

Light curtain LCA-4TR-50-910

- Resolution 50 mm
- Protective field height 910 mm
- Extended range 20 m
- LED indicator for weak signal
- With plug connector M12
- 2 safety outputs (OSSD)
- Installation material is included with the product

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: eai@nt-rt.ru || сайт: <https://euchner.nt-rt.ru/>