

Предохранительные выключатели с транспондерами и защитной блокировкой SET-AP

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: eai@nt-rt.ru || сайт: <https://euchner.nt-rt.ru/>

SAFETY SWITCH CET-AP



Benefits for you

- Safety switch with guard locking and safe guard lock monitoring
- Integrated CES-AP electronics
- A special evaluation unit is not required
- Safety category 4 and PL e according to EN ISO 13849-1 in any installation orientation, head downward/upward/horizontal
- Two safe semiconductor outputs and monitoring output OUT
- Safety outputs with pulsing
- Input (optional) for the connection of feedback loop and start button



124601

CET3-AP-CRA-AH-50F-SA-124601

Non-contact safety switch CET-AP-..., M12, with escape release

- Safety switch with guard locking and integrated evaluation electronics
- Locking force up to 6500 N
- Short circuit monitoring
- 2 safety outputs (semiconductor outputs)
- Category 4 / PL e according to EN ISO 13849-1
- With 1 plug connector M12, 8-pin
- Unicode
- Door monitoring output
- Indication of the door position by LED
- Escape release, 75 mm long
- Approach direction A (delivery state)



119106

CET3-AP-CRA-AH-50F-SH-C2312-119106

Non-contact safety switch CET-AP-..., with plug connector RC18 and escape release

- Safety switch with guard locking and integrated evaluation electronics
- Locking force up to 6500 N
- Short circuit monitoring
- 2 safety outputs (semiconductor outputs)
- Category 4 / PL e according to EN ISO 13849-1
- Plug connector M23 (RC18)
- Unicode
- Door monitoring output
- Indication of the door position by LED
- Teach-in input
- Escape release, 105 mm long
- Approach direction A (delivery state)



114073

CET3-AP-CRA-AH-50F-SI-114073

Non-contact safety switch CET-AP-..., with escape release, for connection to decentralized peripheral systems

- Safety switch with guard locking and integrated evaluation electronics
- Locking force up to 6500 N
- Direct connection to decentralized peripheral systems (e.g. ET200pro)
- Short circuit monitoring
- 2 safety outputs (semiconductor outputs)
- Category 4 / PL e according to EN ISO 13849-1
- With 2 plug connectors M12
- Unicode
- Indication of the door position by LED
- Escape release, 75 mm long
- Approach direction A (delivery state)

**157408**

CET3-AP-CRA-AH-50F-SI-C2312-157408

Non-contact safety switch CET-AP-..., for connection to decentralized peripheral systems

- Safety switch with guard locking and integrated evaluation electronics
- Locking force up to 6500 N
- Direct connection to decentralized peripheral systems (e.g. ET200pro)
- Short circuit monitoring
- 2 safety outputs (semiconductor outputs)
- Category 4 / PL e according to EN ISO 13849-1
- With 2 plug connectors M12
- Unicode
- Escape release, 105 mm long
- Indication of the door position by LED
- Approach direction A (delivery state)

**124594**

CET3-AP-CRA-AH-50F-SI-C2438-124594

Non-contact safety switch CET-AP-..., with escape release, for connection to decentralized peripheral systems

- Safety switch with guard locking and integrated evaluation electronics
- Locking force up to 6500 N
- Connection to decentralized peripheral systems (e.g. ET200pro) via Y-distributor
- Short circuit monitoring
- 2 safety outputs (semiconductor outputs)
- Category 4 / PL e according to EN ISO 13849-1
- With 2 plug connectors M12
- Unicode
- Door monitoring output
- Indication of the door position by LED
- Escape release, 75 mm long
- Approach direction A (delivery state)

**122398**

CET3-AP-CRA-AH-50X-SA-122398

Non-contact safety switch CET-AP-..., M12

- Safety switch with guard locking and integrated evaluation electronics
- Locking force up to 6500 N
- Short circuit monitoring
- 2 safety outputs (semiconductor outputs)
- Category 4 / PL e according to EN ISO 13849-1
- With 1 plug connector M12, 8-pin
- Unicode
- Door monitoring output
- Indication of the door position by LED
- Approach direction A (delivery state)

**122406**

CET3-AP-CRA-AH-50X-SA-122406

Non-contact safety switch CET-AP-..., M12

- Safety switch with guard locking and integrated evaluation electronics
- Locking force up to 6500 N
- Short circuit monitoring
- 2 safety outputs (semiconductor outputs)
- Category 4 / PL e according to EN ISO 13849-1
- With 1 plug connector M12, 8-pin
- Unicode
- Door monitoring output
- Indication of the door position by LED
- Monitoring output DIA
- Approach direction A (delivery state)

**161524**

CET3-AP-CRA-AH-50X-SF-161524

Non-contact safety switch CET-AP-..., M12

- Safety switch with guard locking and integrated evaluation electronics
- Locking force up to 6500 N
- Short circuit monitoring
- 2 safety outputs (semiconductor outputs)
- Category 4 / PL e according to EN ISO 13849-1
- With 1 plug connector M12, 8-pin, can be rotated by 360°
- Unicode
- Door monitoring output
- Indication of the door position by LED
- Approach direction A (delivery state)



111346

CET3-AP-CRA-AH-50X-SI-111346

Non-contact safety switch CET-AP-..., for connection to decentralized peripheral systems

- Safety switch with guard locking and integrated evaluation electronics
- Locking force up to 6500 N
- Direct connection to decentralized peripheral systems (e.g. ET200pro)
- Short circuit monitoring
- 2 safety outputs (semiconductor outputs)
- Category 4 / PL e according to EN ISO 13849-1
- With 2 plug connectors M12
- Unicode
- Indication of the door position by LED
- Approach direction A (delivery state)



121367

CET3-AP-CRA-AH-50X-SI-C2290-121367

Non-contact safety switch CET-AP-..., M12, with wire front release (bowden), for connection to decentralized peripheral systems

- Safety switch with guard locking and integrated evaluation electronics
- Locking force up to 6500 N
- Direct connection to decentralized peripheral systems (e.g. ET200pro)
- Short circuit monitoring
- 2 safety outputs (semiconductor outputs)
- Category 4 / PL e according to EN ISO 13849-1
- With 2 plug connectors M12

- Unicode
- Indication of the door position by LED
- Wire front release (bowden), 5 m
- Approach direction A (delivery state)



124589

CET3-AP-CRA-AH-50X-SI-C2438-124589

Non-contact safety switch CET-AP-..., for connection to decentralized peripheral systems

- Safety switch with guard locking and integrated evaluation electronics
- Locking force up to 6500 N
- Connection to decentralized peripheral systems (e.g. ET200pro) via Y-distributor
- Short circuit monitoring
- 2 safety outputs (semiconductor outputs)
- Category 4 / PL e according to EN ISO 13849-1
- With 2 plug connectors M12
- Unicode
- Door monitoring output
- Indication of the door position by LED
- Approach direction A (delivery state)



157287

CET3-AP-CRA-CH-50F-SA-C2312-157287

Non-contact safety switch CET-AP-..., M12

- Safety switch with guard locking and integrated evaluation electronics
- Locking force up to 6500 N
- Short circuit monitoring
- 2 safety outputs (semiconductor outputs)
- Category 4 / PL e according to EN ISO 13849-1
- With 1 plug connector M12, 8-pin
- Multicode
- Door monitoring output OUT
- Monitoring output OUT
- Indication of the door position by LED
- Escape release, 105 mm long
- Approach direction A (delivery state)

**121579**

CET3-AP-CRA-CH-50X-SA-121579

Non-contact safety switch CET-AP-..., M12

- Safety switch with guard locking and integrated evaluation electronics
- Locking force up to 6500 N
- Short circuit monitoring
- 2 safety outputs (semiconductor outputs)
- Category 4 / PL e according to EN ISO 13849-1
- With 1 plug connector M12, 8-pin
- Multicode
- Door monitoring output
- Indication of the door position by LED
- Approach direction A (delivery state)

**122409**

CET3-AP-CRA-CH-50X-SA-122409

Non-contact safety switch CET-AP-..., M12

- Safety switch with guard locking and integrated evaluation electronics
- Locking force up to 6500 N
- Short circuit monitoring
- 2 safety outputs (semiconductor outputs)
- Category 4 / PL e according to EN ISO 13849-1
- With 1 plug connector M12, 8-pin
- Multicode
- Door monitoring output
- Indication of the door position by LED
- Monitoring output DIA
- Approach direction A (delivery state)

**122415**

CET4-AP-CRA-AH-50X-SA-122415

Non-contact safety switch CET-AP-..., M12

- Safety switch with guard locking and integrated evaluation electronics
- Locking force up to 6500 N
- Short circuit monitoring
- 2 safety outputs (semiconductor outputs)
- Category 4 / PL e according to EN ISO 13849-1
- With 1 plug connector M12, 8-pin
- Unicode
- Door monitoring output
- Indication of the door position by LED
- Approach direction A (delivery state)



112082

CET4-AP-CRA-AH-50X-SI-112082

Non-contact safety switch CET-AP-..., for connection to decentralized peripheral systems

- Safety switch with guard locking and integrated evaluation electronics
- Locking force up to 6500 N
- Direct connection to decentralized peripheral systems (e.g. ET200pro)
- Short circuit monitoring
- 2 safety outputs (semiconductor outputs)
- Category 4 / PL e according to EN ISO 13849-1
- With 2 plug connectors M12
- Unicode
- Indication of the door position by LED
- Approach direction A (delivery state)



126763

CET4-AP-CRA-AH-50X-SI-C2438-126763

Non-contact safety switch CET-AP-..., for connection to decentralized peripheral systems

- Safety switch with guard locking and integrated evaluation electronics
- Locking force up to 6500 N
- Connection to decentralized peripheral systems (e.g. ET200pro) via Y-distributor
- Short circuit monitoring
- 2 safety outputs (semiconductor outputs)
- Category 4 / PL e according to EN ISO 13849-1
- With 2 plug connectors M12

- Unicode
- Door monitoring output
- Indication of the door position by LED
- Approach direction A (delivery state)



161577

CET4-AP-CRA-AH-50X-SI-C2509-161577

Non-contact safety switch CET-AP-..., M12, with wire front release (bowden), for connection to decentralized peripheral systems

- Safety switch with guard locking and integrated evaluation electronics
- Locking force up to 6500 N
- Connection to decentralized peripheral systems (e.g. ET200pro) via Y-distributor
- Short circuit monitoring
- 2 safety outputs (semiconductor outputs)
- Up to category 4 / PL e according to EN ISO 13849-1
- With 2 plug connectors M12
- Unicode
- Door monitoring output
- Indication of the door position by LED
- Wire front release (bowden), 3 m, automatic return
- Approach direction A (delivery state)



161178

CET4-AP-CRA-CH-50F-SA-161178

Non-contact safety switch CET-AP-..., M12

- Safety switch with guard locking and integrated evaluation electronics
- Locking force up to 6500 N
- Short circuit monitoring
- 2 safety outputs (semiconductor outputs)
- Category 4 / PL e according to EN ISO 13849-1
- With 1 plug connector M12, 8-pin
- Multicode
- Door monitoring output
- Indication of the door position by LED
- Escape release, 75 mm long
- Approach direction A (delivery state)



122413

CET4-AP-CRA-CH-50X-SA-122413

Non-contact safety switch CET-AP-..., M12

- Safety switch with guard locking and integrated evaluation electronics
- Locking force up to 6500 N
- Short circuit monitoring
- 2 safety outputs (semiconductor outputs)
- Category 4 / PL e according to EN ISO 13849-1
- With 1 plug connector M12, 8-pin
- Multicode
- Door monitoring output
- Indication of the door position by LED
- Approach direction A (delivery state)

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: eai@nt-rt.ru || сайт: <https://euchner.nt-rt.ru/>